



## **24 HOUR TIME CLOCK (Model TMR-LX)**

### **APPLICATION :**

The **TMR-LX Time Clock** can be added to the **LX-20, LX-30 or LX-40 Power Center** to program the daily operating time of your pool cleaner.

**NOTE : A relay kit (model RLY-LX) must be added to the system to activate the pool cleaner pump.**

The **TMR-LX** can also be added to the **LX-36 Power Center**.

In this instance, it can only be used to program the daily operating times of Circuit #1.

### **INSTALLATION :**

1. Loosen lock screw, and open hinged faceplate in left-side compartment of Power Center.
2. Remove hole plug from faceplate.
3. Insert **TMR-LX Time Clock** through hole in faceplate, and secure using the 3 mounting screws provided.
4. Plug connector onto printed circuit board at appropriate terminal:  
**LX-20:** Plug into CLEANER terminal.  
**LX-30:** Plug into CLNR TIMER terminal.  
**LX-36:** Plug into TIMER terminal.  
**LX-40:** Plug into CLEANER terminal.

### **OPERATION :**

**To set the correct time of day :** Rotate the dial in a clockwise direction until the hours and minutes line up with the white arrow at eight o'clock position on clock face.

**Pay particular attention to the AM and PM sections of dial.**

**To program operating time :** Depress number of sections around the perimeter of the dial by pushing towards the center. For each section depressed, the equipment will operate for 15 minutes.

**NOTE : At the LX-30 and LX-40 Power Center, it will not be possible to activate pool cleaner unless the Remote Control switch is connected.**